

Seattle Fire Prevention Division

220 3rd Avenue South Seattle, WA 98104 (206) 385-1450 SFD_FMO_SystemsTesting@seattle.gov

SYSTEM TEST REPORT

FIRE ALARM	STATUS		
☐ Confidence Test ☐ Deficiency Repair Test	☐ Red ☐ Yellow ☐ White		
Occupancy Information			
Premises Name:	Premises Address:		
Contact Name:	Contact Phone:		
Contact Address:	Contact Email:		
Monitoring required?			
Central Station Monitoring:*	Dialer		
Monitoring Company Name:	Reporting Type		
Monitoring Company Phone:	☐ Cellular ☐ Radio ☐ AES		
Fire Alarm Inventory (M-mandatory)			
Fire Alarm Panel Unit ID (TCE will assign one per system) (M):			
NFPA 72 Edition (Year):			
Smoke Detector Sensitivity (required every 5 yrs, after passin	g 1st annual calibration test) –		
Last Test Date (month/year):			
Smoke Detector Sensitivity – Test Due Date (month/year):			
FACP & Annunciators			
Fire Alarm Control Panel/Unit Location (M):			
Fire Alarm Panel Manufacture	Fire Alarm Panel Model:		
FACP – location of key (M):	Annunciator location (M):		
Notification Power Yes No	Notification Power		
Expander(s) Installed?	Expander(s) Location:		
Expander(s) Installed? Note: This section is optional except at time of new system as	·		
Expander(s) Installed?	·		
Note: This section is optional except at time of new system ac	·		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors	ceptance. Please enter number of devices or items in the # of devices/items Smoke detectors - Regular		
Note: This section is optional except at time of new system ac system. Initiating Devices # of devices/items	ceptance. Please enter number of devices or items in the # of devices/items Smoke detectors - Regular Smokes – above ceiling		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals	ceptance. Please enter number of devices or items in the # of devices/items Smoke detectors - Regular Smokes – above ceiling Smokes – under floor		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire)	# of devices/items Smoke detectors - Regular Smokes – above ceiling Smokes – under floor Sprinkler valve tamper switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular	# of devices/items Smoke detectors - Regular Smokes – above ceiling Smokes – under floor Sprinkler valve tamper switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations)	# of devices/items Smoke detectors - Regular Smokes – above ceiling Smokes – under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances Bells, chimes	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances Bells, chimes	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances Bells, chimes Exterior sprinkler alarm bell	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo Horns only		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats — above ceiling/attic Heats — regular Heats — under floor Pull stations (manual stations) Notification Appliances Bells, chimes Exterior sprinkler alarm bell Speakers	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo Horns only Strobes only		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances Bells, chimes Exterior sprinkler alarm bell Speakers Speaker strobes	# of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo Horns only Strobes only		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances Bells, chimes Exterior sprinkler alarm bell Speakers Speaker strobes Auxiliary Equipment	# of devices or items in the # of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo Horns only Strobes only Low frequency sounders		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats — above ceiling/attic Heats — regular Heats — under floor Pull stations (manual stations) Notification Appliances Bells, chimes Exterior sprinkler alarm bell Speakers Speaker strobes Auxiliary Equipment Auto door release	# of devices or items in the # of devices/items Smoke detectors - Regular Smokes — above ceiling Smokes — under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo Horns only Strobes only Low frequency sounders Fire/smoke dampers		
Note: This section is optional except at time of new system as system. Initiating Devices # of devices/items Beam detectors Duct detectors Heat trace cable supervisory signals Thermal alarm wire (protector wire) Heats – above ceiling/attic Heats – regular Heats – under floor Pull stations (manual stations) Notification Appliances Bells, chimes Exterior sprinkler alarm bell Speakers Speaker strobes Auxiliary Equipment Auto door release Auto door unlock	# of devices or items in the # of devices/items Smoke detectors - Regular Smokes – above ceiling Smokes – under floor Sprinkler valve tamper switches Sprinkler flow switches High/low air switches Other supervisory switches Horn/strobe combo Horns only Strobes only Low frequency sounders Fire/smoke dampers Generators		

Cta	Fire fighter phone sets	Other (DAS/VESDA, F	ARS)		
Stai	irway Door Locks	Other leaking devices			
	Electric bolt Electric strike	Other locking devices	•		
Dat	tery Info				
buι		Number of batte	rioc		
	Location Ratter (voltage (no load)):				
	Battery voltage (no load):	Battery Size (AH)		- t.l. /	
	Battery voltage (full load):	Date due for nex	tt testing (mor	itn/year):	
	Charge circuit voltage:				
Pov	ver Expander Panels				
•	Number of units				
	pection & Testing Agency Information	Dhana			
	npany Name:	Phone:			
Aac	lress:	Emergency Phone:			
		Email:			
·	pector/Tester Information				
-	pector Name:				
	tification No.:				
	t Information e of Test:				
			□ N4 a rath l		
	t Type: Annual Quarterly	Semi-annual	Monthl	У	
Are	a of building tested and general description of testing pe	rformed on this report (text field)		
	s is the final report for the testing year, indicating complets. (Reports confirming tests of 100% of devices must be		ndatory	☐ Yes	☐ No
The	items on the checklists below shall be inspected and tes	ted. This list does not co	onstitute all of	the required	inspecting
	testing of the fire and life safety system. Refer to the CL				
the	${\tt MANUFACTURER'S\ INSTRUCTIONS\ for\ weekly,\ monthly,}$	and quarterly inspecting	g and testing r	equirements.	ONLY
SEL	ECT N/A FOR ITEMS THAT DO NOT EXIST AT THE BUILDIN	IG, DO NOT USE N/A TO	INDICATE TH	AT A TEST OR	RESULT IS
NO.	T AVAILABLE.				
PRE	-TEST CHECKS				
AV(DID "FALSE ALARMS" TO FIRE DEPARTMENT BY PUTTING	THE FIRE ALARM SYSTE	M IN TEST MC	DE. Failure to	place the
Fire	Alarm System (FAS) into test mode and/or taking other	precautions to may caus	se preventable	e alarms.	
1	The building occupants were notified.		Yes	☐ No	☐ N/A
2	The onsite supervisory station was notified.		Yes	☐ No	☐ N/A
3	The Central Station Monitoring Service was notified to p	place FAS in test	□ Vaa		□ N1/A
	mode.		Yes	☐ No	☐ N/A
GEN	NERAL				
4	The key to the panel is available at the FACP.		☐ Yes	☐ No	□ N/A
5	The operating instructions are available at the FACP, cal approved location.	oinet, or other	☐ _{Yes}	□ _{No}	
6	Materials and equipment needed to restore pull station	s are available at the			
	main panel, e.g. glass rods, and plates; keys and allen w		☐ Yes	□ No	☐ N/A
	ARM PANEL				
7	The FACP operates on AC power.		Yes	☐ No	_
8	If the system has batteries, the FACP operates on Batter	• •	Yes	☐ No	☐ N/A
9	If the system has emergency generator/standby power, on emergency generator/standby power.	the FACP operates	☐ Yes	☐ No	□ N/A
10	If the system has battery or standby power, the trouble properly and a trouble signal comes on with AC power of		☐ Yes	☐ No	□ N/A

INIT	TATING DEVICES AND NOTIFICATION APPLIANCES			
11	Initiating & notification appliances tested operate properly on AC power.	Yes	☐ No	
12	If system has generator/standby power, initiating and notification appliances	□ Voc	□ No	□ NI/A
	tested operate properly on generator/standby power.	Yes	☐ No	□ N/A
13	If system has batteries, initiating and notification appliances tested operate	Yes	□No	□ N/A
	properly on battery power.			
14	100% of the INITIATING DEVICES per circuit that were tested and included as		_	
	part of this report were in accordance with the NFPA 72 Chapter 14	Yes	☐ No	
	standards referenced by the current fire code.			
	e: 2 or 20%, whichever is greater, of restorable fixed-temperature, spot-type hear	t detectors n	eed to be test	ed annually.
	ords shall be kept to ensure that every detector is tested every five years.			
15	The sensitivity test for smoke detectors is up-to-date in accordance with NFPA 72. (After passing the 2nd required calibration test, sensitivity may be calibrated once every 5 years [2016 NFPA 72 Sec 14.4.4.3]).	Yes	No	□ N/A
	Date most recent smoke detector sensitivity test was passed:			
16	100% of the AUDIBLE NOTIFICATION APPLIANCES per circuit that were tested and included as part of this report were in accordance with 2016 NFPA 72 Chapter 14.	☐ Yes	☐ No	
17	The audible notification appliances tested operate at the levels required by NFPA 72.	☐ Yes	□ No	
18	The audible notification appliances tested in residential units generate a minimum of 75dBA at the pillow in the sleeping areas.	Yes	☐ No	□ N/A
19	100% of the VISUAL NOTIFICATION APPLIANCES per circuit that were tested and included as part of this report were in accordance with 2016 NFPA 72	Yes	No	□ N/A
20	Positive alarm sequence programming and panel perform to standards.	☐ Yes	□No	□ N/A
ВАТ	TERIES			
20	Battery voltage (no load):			
21	Battery voltage (full load):			
	New batteries installed? Battery installation date: [current me	onth/vearl:		
	Charge circuit voltage:	,,,,		
	ERFACE DEVICES			
The	FACP received signals from the following Interface devices:	Cinculat	.:	Onomotion
Tes	red by:	Simulat	lion	Operation
24	Emergency Generator(s)	Yes	☐ No	□ N/A
25	Flow Switch(es)	☐ Yes	☐ No	□ N/A
26	Supervisory Switch(es)	☐ Yes	☐ No	☐ N/A
27	Range Hood Suppression System(s)	Yes	☐ No	☐ N/A
28	Dry Chemical System(s)	☐ Yes	☐ No	☐ N/A
29	Clean Agent System(s)	☐ Yes	☐ No	☐ N/A
30	Pre-action Systems(s)	Yes	☐ No	☐ N/A
31	Fire Pump(s)	☐ Yes	☐ No	☐ N/A
32	CO2 System(s)	☐ Yes	☐ No	☐ N/A
OTHER EQUIPMENT CONTROLLED BY FACP				
	following Fire Safety Functions responded to signals from the FACP:	Simulat	ion 🗆	Operation
	ted by:			
Note: This section replaces the Sequence Test Form. The checks in this section are only required during one of the quarterly tests. The functions in this section require testing during the annual confidence test for all other buildings.				
32	Fan Controls	Yes	☐ No	□ N/A
33	Smoke & Fire Dampers and Combination Fire/Smoke Dampers	☐ Yes	☐ No	☐ N/A

34	Elevator Recall system	☐ Yes	☐ No	□ N/A
35	Elevator Shunt Switch(es)	☐ Yes	☐ No	□ N/A
	Note: Fire alarm tech only tests/reports on elevator shunt switches that are			
	connected to fire alarm.			
36	Shaft Pressurization System	☐ Yes	☐ No	□ N/A
37	Magnetic Door Holders (see inventory)	☐ Yes	☐ No	☐ N/A
38	Door Lock Devices (see inventory)	☐ Yes	☐ No	□ N/A
39	Stage Amplifier/Audio-Visual Shut Down	☐ Yes	☐ No	☐ N/A
40	General alarm automatic time delay (minutes)	☐ Yes	☐ No	□ N/A
41	Remote Annunciator Panels	☐ Yes	☐ No	☐ N/A
COI	MMUNICATION EQUIPMENT			
42	All fire fighter phone sets function properly.	☐ Yes	☐ No	☐ N/A
43	All fire fighter phone jacks function properly.	☐ Yes	☐ No	□ N/A
44	All fire fighter phone indicating signals at the FACP work properly.	☐ Yes	☐ No	□ N/A
45	The public address equipment at the FACP works properly.	Yes	☐ No	□ N/A
ALA	RM PANEL MONITORING			
46	A signal was received at the Central Station monitoring company.	Yes	☐ No	□ N/A
STA	IRWAY DOOR LOCKS [if no stairways in building, skip this section and proceed	to final check	s]	
This	building has stairways:	☐ Yes		□ N/A
47	All stairway door locking devices release simultaneously upon activation of			
	the fire alarm system from anywhere in the building.	Yes	☐ No	□ N/A
48	All stairway door locking devices release simultaneously upon activation from			_ ,
	the fire command center.	Yes	☐ No	☐ N/A
49	The door(s) to the roof unlocks upon activation of the fire alarm system.	☐ Yes	☐ No	□ N/A
50	All of the doors appear to close and latch, or the responsible party has been	_		_ ,
	advised of that issues were observed and their requirement to address the	☐ Yes	☐ No	□ N/A
	issues separate from the fire alarm ITM.			, ,,,
FIN	AL CHECKS, MANDATORY TAGGING, AND REPORTS			
	the Fire Alarm/monitoring system back into service and/or other precautionary	measures that	were made to	restore fire
	m system to normal operation (includes removal of protective coverings.)		, 11010 111000 10	
	A current red (impaired), yellow (deficient) or white (normal operations) tag			
	was placed on the fire alarm control panel indicating the system's status	☐ Yes	☐ No	
	consistent with my inspection today.			
	The color of the tag is:	Red	☐ Yellow	White
52	I will provide a copy of the confidence test report to the owner.	☐ Yes	☐ No	Willice
53	I will submit this test report to the fire department through TCE.	☐ Yes	□ No	
_	accepting this statement I, the certified technician shown on this form, certify that			s) has heen
-	perly inspected for functional operation in accordance with the current Fire Code			
-	sdiction and NFPA Standards adopted by the FC for this system. Any deficiencies			
	n reported to the building Owner/Manager for corrective action.	Tourid are not	ed in the repor	t and nave
bee	I am authorized to submit this report for the certified	(1	Initials of Emplo	
	technician who has accepted this statement.	(1	initials of Emplo	Эусс,
SIG	NATURE (OPTIONAL)			
3.0				
Sigr	nature of Technician			
Sigr	nature of Building Representative			

System Testing Reports Must Be Submitted Online

Submit reports to www.thecomplianceengine.com